

JC810 U.S. PTO
08/21/00

8-23-00

A

PTO/SB/05 (4/98)

Approved for use through 9/30/2000. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Type a plus sign (+) inside this box ☐

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No.

M 6636 CC/CSAP

First Inventor or Application Identifier

Gross, Stephen F.

Title

GRAFFITI REMOVER, PAINT STRIPPER,
DEGREASER

Express Mail Label No.

EL545113995US

PTO
09/643141
c846 U.S.

08/21/00

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages] 29
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R&D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☐ Drawing(s) (35 U.S.C. 113) [Total Sheets]
4. ☒ Oath or Declaration (UNEXECUTED) (Total Pages) 3
 - a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 15 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
inventor(s) named in the prior application, see
37 C.F.R. §§ 1.63(d)(2) and 1.33(b)

*NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY
FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT
IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure
Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ *Small Entity
Statement(s) ☐ Statement filed in prior application,
(PTO/SB/09-12) Status still proper and desired
14. ☐ Certified Copy of Priority Document(s)
(If foreign priority is claimed)
15. ☐ Other

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP)

of prior application No. _____ / _____

Prior application information: Examiner _____

Group / Art Unit _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label



or ☐ Customer address below

23657

(Insert Customer No. or Attach bar code label here)

Name	Steven J. Trzaska				
Address					
City	State	Zip Code			
Country	Telephone	610-278-4929	Fax	610-278-6548	

Name (Print/Type)	Steven J. Trzaska	Registration No. (Attorney/Agent)	36,296
Signature		Date	August 22, 2000

Burden Hour Statement: this form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

TITLE OF THE INVENTION:

Graffiti Remover, Paint Stripper, Degreaser

CROSS-REFERENCE TO RELATED APPLICATIONS:

5 This application claims the benefit of copending provisional application
serial number 60/155,330 filed on September 22, 1999.

**STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH
OR DEVELOPMENT:**

10 Not Applicable.

BACKGROUND OF THE INVENTION:

The present invention generally relates to a cleaning composition.
More particularly, the invention relates to a novel cleaning formulation having
15 superior cleaning ability which is readily biodegradable, low in toxicity and
volatility, neutral in pH and primarily naturally derived.

General purpose household cleaning compositions for hard surfaces
such as metal, glass, ceramic, plastic and linoleum surfaces are commercially
available in both powdered and liquid form. Powdered cleaning compositions
20 consist mainly of builder or buffering salts such as phosphates, carbonates,

and silicates and although such composition may display good inorganic soil removal, they exhibit inferior cleaning performance on organic soils such as greasy/fatty/oily soils.

Liquid cleaning compositions, on the other hand, have the great
5 advantage that they can be applied onto hard surfaces in a neat or concentrated form so that a relatively high level of surfactant material is delivered directly to the soil. Moreover, it is a rather more straightforward task to incorporate high concentrations of anionic or nonionic surfactant in a liquid rather than a granular composition. For both of these reasons, therefore,
10 liquid cleaning compositions have the potential to provide superior grease and oily soil removal over powdered cleaning compositions.

Nevertheless, liquid cleaning compositions suffer a number of drawbacks which can limit their consumer acceptability. They generally contain little or no detergency builder salts and consequently they tend to
15 have poor cleaning performance on particulate soil and also lack effectiveness under varying water hardness levels. In addition, they can suffer problems relating to homogeneity, clarity, and viscosity when used by consumers. Moreover, the higher in-use surfactant concentration necessary for improved grease and soil removal causes further problems relating to
20 extensive suds formation which requires frequent rinsing and wiping on the part of the consumer.

One solution to the above-identified problems has involved the use of saturated and unsaturated terpenes, in combination with a polar solvent, in

order to increase the cleaning effectiveness of the hard surface cleaner and control sudsing. A problem associated with the use of terpenes such as, for example, d-limonene, is that their price, as a raw material, tends to fluctuate wildly. Consequently, the cost to manufacture hard surface liquid cleaners
5 containing terpene solvents is financially disadvantageous to both producers and consumers.

Other solvents which are often employed in hard surface cleaning compositions, instead of terpenes, include those derived from aliphatic, aromatic and halogenated hydrocarbons. Their use, however, is undesirable
10 for environmental reasons due to their limited biodegradation.

Consequently, it would be highly desirable to employ a solvent which is both readily biodegradable and is not subject to any significant fluctuations in pricing for the raw material.

15 **BRIEF SUMMARY OF THE INVENTION:**

The present invention is directed to a terpene-free cleaning composition containing:

(a) a C_{1-4} alkyl ester of a C_{6-22} saturated or unsaturated carboxylic acid;
and

20 (b) a cyclic ketone, wherein (a) and (b) are employed at a ratio by weight of from about 10:1 to about 1:10.

The present invention is also directed to a terpene-free cleaning composition containing:

(a) from about 2 to about 12% by weight of an oil-soluble anionic surfactant;

(b) from about 0.2 to about 6% by weight of a water-soluble anionic surfactant;

5 (c) from about 3 to about 96% by weight of a primary solvent consisting of a C₆-C₁₄ methyl ester;

(d) from about 2 to about 14% by weight of a short-chain cosurfactant; and

(e) remainder, water, all weights being based on the total weight of the
10 composition.

The present invention is also directed to a process for cleaning a substrate involving contacting the substrate with a cleaning-effective amount of either of the above-disclosed terpene-free cleaning compositions.

15 **BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING:**

NOT APPLICABLE.

DETAILED DESCRIPTION OF THE INVENTION:

Other than in the operating examples, or where otherwise indicated, all
20 numbers expressing quantities of ingredients or reaction conditions used herein are to be understood as being modified in all instances by the term "about".

The removal of undesirable aged paints, coatings, greases, and the

like from various substrates is accomplished by two mechanisms, namely, dissolution and lifting. Dissolution is when the undesirable material is dissolved from the substrate by a solvent. Lifting is when the solvent penetrates into the undesirable material and causes it to swell. As a result of the swelling the material, whether it be a paint, coating or the like, wrinkles and lifts (separates) from the substrate, allowing it to then be easily removed from the substrate's surface.

It has surprisingly been discovered that a highly effective cleaning composition, free of terpenes, which possesses both the dissolution and lifting mechanisms, can be formulated by combining a C₁₋₄ alkyl ester of a C₆₋₂₂ saturated or unsaturated carboxylic acid, acting as a primary solvent to facilitate dissolution, with a cyclic ketone which provides the lifting mechanism.

The primary solvent used in the present invention is a C₁₋₄ alkyl ester of a C₆₋₂₂ saturated or unsaturated carboxylic acid. The use of an alkyl ester as a solvent in cleaning compositions is significantly more desirable than conventional solvents, such as terpenes and hydrocarbon derivatives, for both environmental and economic reasons.

A particularly preferred C₁₋₄ alkyl ester of a C₆₋₂₂ saturated or unsaturated carboxylic acid for use in the present invention is a methyl ester corresponding to formula I:



wherein R₁ is an alkyl radical having from about 6 to about 14 carbon atoms.

They are derived by the esterification of a fatty acid with methanol. Preferred methyl esters are those derived from the esterification of unsaturated fatty acids having from about 8 to about 10 carbon atoms. Suitable fatty acids from which the fatty acid esters may be derived include, but are not limited to, coconut and other vegetable oils, tallow, etc.

Suitable cyclic ketones for use in the cleaning composition of the present invention include, but are not limited to, cyclopentanone, cyclohexanone, cycloheptanone, and the like. A particularly preferred cyclic ketone is cyclohexanone.

According to one embodiment of the present invention, there is thus provided a terpene-free cleaning composition containing: (a) a C_{1-4} alkyl ester of a C_{6-22} saturated or unsaturated carboxylic acid, preferably a C_{6-14} methyl ester; and (b) a cyclic ketone, preferably a cyclohexanone, wherein (a) and (b) are employed at a ratio by weight of from about 10:1 to about 1:10, and preferably about 2:1.

The above-disclosed composition can be applied onto any type of substrate having an undesirable paint, coating or other material thereon, in order to dissolve and/or lift it therefrom.

According to another aspect of the present invention, there is provided a terpene-free cleaning composition having improved high and low temperature stability which may also be easily rinsed from a cleaned surface. These properties are imparted to the composition through the use of oil-soluble and/or water-soluble anionic surfactants.

Suitable oil-soluble anionic surfactants which may be employed in the present invention include, but are not limited to, amine salts of dodecylbenzenesulfonic acid, calcium salts of dodecylbenzenesulfonic acid, and phosphate esters. A particularly preferred oil-soluble anionic surfactant is the isopropylamine salt of dodecylbenzenesulfonic acid.

Suitable water-soluble anionic surfactants which may be employed in the present invention include, but are not limited to, water-soluble salts of alkyl benzene sulfonates, alkyl sulfates, alkyl polyethoxy ether sulfates, paraffin sulfonates, alpha-olefin sulfonates and sulfosuccinates, alpha-sufocarboxylates and their esters, alkyl glyceryl ether sulfonates, fatty acid monoglyceride sulfates and sulfonates, and alkyl phenol polyethoxyether sulfates.

Other suitable water-soluble anionic surfactants include the water-soluble salts or esters of alpha-sulfonated fatty acids containing from about 6 to about 20 carbon atoms in the fatty acid group and from about 1 to about 10 carbon atoms in the ester group.

Particularly preferred anionic surfactants for use in the present invention include the isopropylamine salt of a C_{10-14} alkyl benzene sulfonic acid, and/or a C_{8-14} fatty alcohol sulfate.

In the event that an anionic surfactant is employed, it will typically be present in the composition in an amount of from about 0.1 to about 15% by weight, preferably from about 3 to about 12% by weight, and most preferably from about 5 to about 10% by weight, based on the weight of the

composition.

Another consideration that needs to be taken into account when formulating a terpene-free cleaning composition in accordance with the present invention relates to the cost of each individual component. In order to
5 reduce costs, it is advisable to introduce a certain amount of water into the composition, thereby reducing the amount of actives needed to formulate the cleaning composition.

However, in order to maintain a high level of cleaning capability in the water containing version of the cleaning composition, it is advisable that a co-
10 surfactant, preferably a short-chain co-surfactant, also be employed in the composition.

Suitable short-chain co-surfactants for use in the present invention include, but are not limited to, C₃-C₆ alcohols, glycols, glycol ethers, pyrrolidones and glycol ether esters. A particularly preferred short-chain
15 cosurfactant is propylene glycol n-butyl ether.

Thus, according to another embodiment of the present invention, there is provided a terpene-free cleaning composition containing: (a) from about 2 to about 12% by weight, preferably from about 4 to about 10% by weight, and most preferably from about 6 to about 8% by weight, of an oil-soluble anionic
20 surfactant, (b) from about 0.2 to about 6% by weight, preferably from about 0.5 to about 3% by weight, and most preferably from about 1 to about 2% by weight, of a water-soluble anionic surfactant, (c) from about 3 to about 96% by weight, preferably from about 25 to about 65% by weight, and most

preferably from about 40 to about 50% by weight, of a C₆-C₁₄ methyl ester solvent, (d) from about 2 to about 14% by weight, preferably from about 5 to about 12% by weight, and most preferably from about 8 to about 10% by weight, of a short-chain cosurfactant, and (e) remainder, water, all weights
5 being based on the total weight of the composition.

The advantage of employing a cyclic ketone in the cleaning composition of the present invention is that it facilitates the removal of paints and coatings having a polymeric matrix such as, for example, polyurethane, epoxy, and alkyd enamels. Therefore, in those instance where the removal of
10 polymeric coating compositions is desired, a cyclic ketone should be incorporated into the composition in an amount of from about 1 to about 35% by weight, preferably from about 5 to about 25% by weight, and most preferably from about 10 to about 20% by weight, based on the weight of the composition.

15 Since methyl esters are subject to hydrolysis under alkaline conditions, it is imperative that the pH of the hard-surface cleaning composition be less than about 9, and preferably in the range of from about 6 to about 9.

The terpene-free cleaning composition of the present invention may be employed as either a neat solution or a microemulsion. Its use as a
20 microemulsion, however, affords it the greatest degree of cost/performance. In this form it is an oil continuous microemulsion characterized by a high level of thermal stability, ranging from about 10 to about 70°C. However, in order to achieve this level of thermal stability, the methyl ester component and

water should be present in the composition in a ratio by weight of from about 50:1 to about 1:4, preferably from about 5:1 to about 1:2, and most preferably about 1.5:1.

Auxiliaries may be incorporated into the cleaning composition of the present invention without departing from the spirit thereof. Examples of suitable auxiliaries which may be used include, but are not limited to, nonionic surfactants, amphoteric surfactants, zwitterionic surfactants, pH buffering agents, corrosion inhibitors, dyes, perfumes, enzymes, preservatives, thickeners, hydrotropes, and the like.

According to another embodiment of the present invention, there is provided a process for cleaning a hard surface involving contacting the hard surface with the above-disclosed composition.

The cleaning compositions according to the invention can be used in a wide variety of applications which include, but are not limited to, the removal of grease, oil, ink, chewing gum and paint from hard and porous surfaces including all kinds of natural and synthetic fabrics in both industrial-institutional and consumer applications. Examples of the disparate types of applications include, but are not limited to, the use of the cleaning compositions according to the invention as water rinsable paint brush cleaners for brushes having both natural and synthetic bristles. Another use is as a cleaner for human skin and nails such as hand and finger nail cleaner for the removal of paints, greases, glues, nail polish and the like. The cleaning compositions according to the invention can also be used as a spot cleaner

for removing grease, oil and paints from carpets and rugs and as a prespotter in laundry applications for the removal of stains from fabrics. Other applications include the removal of grease such as lithium and molybdenum greases from steel and concrete surfaces such as, for example, wheel bearings or garage floors having grease and oil stained tire tracks and the like. The cleaning compositions according to the invention can also be used to clean the concrete and metal surfaces of off-shore oil drilling platforms.

The cleaning compositions according to the invention can also contain an effective amount of odor masking agents such as natural products, for example, essential oils; aroma chemicals; perfumes and the like. Examples of natural products include, but are not limited to, ambergris, benzoin, castoreum, civet, clove oil, galbanum, jasmine, rosemary oil, sandalwood, and the like. Examples of aroma chemicals include, but are not limited to, isoamyl acetate (banana); isobutyl propionate (rum); methyl anthranilate (grape); benzyl acetate (peach); methyl butyrate (apple); ethyl butyrate (pineapple); octyl acetate (orange); n-propyl acetate (pear); ethyl phenyl acetate (honey). The cleaning compositions according to the invention can contain any combination of the above types of compounds. An effective amount of such odor masking agents in the cleaning compositions according to the invention is any amount necessary to produce an odor masking effect or reduce an unwanted odor to an acceptable level. Such an amount will be readily determinable by those skilled in the art. The amount of odor masking agent will typically vary from about 0.25% to about 2.50% by weight of the

cleaning composition with the preferred amount being from about 0.4% to about 1.0%.

The cleaning compositions according to the invention can be packaged in a variety of containers such as steel, tin, and aluminum cans and plastic and glass bottles. The cleaning compositions can be applied by a variety of application means which include, but are not limited to, spraying such as in aerosol form or other spraying means such as by standard spray nozzles when used to remove dirt and grime from trucks and railroad cars; brush application; dipping; coating; application in gel form such as from a squeeze bottle or brush. The cleaning compositions according to the invention can be formulated in gel form by the addition of an effective amount of a gelling agent such as fumed silica, organic gums, polymers, copolymers, paraffin wax, bentonite clay, and cellulose ethers such as methyl cellulose and hydroxypropyl methyl cellulose commercially available as METHOCEL® cellulose ethers, trademark products of Dow Chemical.

An in-can corrosion problem can arise when the cleaning compositions according to the invention are packaged in cans. Cans, and particularly aerosol cans, are generally made from steel and are, therefore, susceptible to corrosion by products containing water. Products containing water, such as the composition according to the invention, require the addition of a corrosion inhibitor to prevent corrosion of the can and contamination of the formulation in the can. When the formulation according to the invention is in the form of a microemulsion, the microemulsion is susceptible to destabilization by the

addition of ions to the formulation. It is therefore necessary to use a corrosion inhibitor that will not contribute to the destabilization of the microemulsion.

Corrosion inhibitors that are compatible with the microemulsion composition according to the invention must be selected such that they do not contribute
5 an amount of ions to the formulation that will destabilize the microemulsion.

Preferably the inhibitor will be a molecule that has both an oil soluble portion and a water soluble portion. It has been found that an amphoteric surfactant containing an amine functionality in an amount of from about 0.05% to about 2% by weight, and preferably from about 0.25 % to about 1.0%, acts as a

10 corrosion inhibitor when combined with the microemulsion composition according to the invention, does not break the microemulsion and is effective in prevention of corrosion. Examples of suitable corrosion inhibitors include the DERIPHAT® amphoteric surfactants, particularly advantageous is DERIPHAT® 151-C, available from Henkel Corporation, Ambler PA. Other

15 corrosion inhibitors that can be used with the composition according to the invention include, but are not limited to, amine soaps of fatty acids and fatty alkanolamides such as the C₈ to C₁₈ fatty alkanolamides, examples of which include STANDAMID® alkanolamides, available from Henkel Corporation.

Such corrosion inhibitors can also be used for post-application anti-corrosion
20 effects on surfaces that will rust or corrode because of the presence of water in the cleaning compositions according to the invention such as on metal surfaces such as iron and steel and the like. The amount of the corrosion inhibitors required for post-application purposes is any amount effective to

inhibit or prevent corrosion of a metal surface onto which the cleaning compositions according to the invention are applied.

It should be noted that additional auxiliaries may also be incorporated into the hard surface cleaning composition of the present invention without
5 departing from the spirit of the invention. Examples of suitable auxiliaries which may be used include, but are not limited to, amphoteric surfactants, zwitterionic surfactants, pH buffering agents, dyes, perfumes, enzymes, preservatives, thickeners, hydrotropes, corrosion inhibitors and the like.

A particularly preferred auxiliary component for use in the present
10 invention is a thickening agent used for thickening the composition. Employing a thickening agent in the composition enables the composition to be applied onto vertical surfaces without any attendant dripping or run-off therefrom, and also inhibits dissipation of the composition into porous substrates such as brick or concrete. While any suitable thickening agent may
15 be employed including, but not limited to, stearates and organoclay compounds, a particularly preferred thickening agent is tetraalkyl ammonium bentonite due to its stability over a broad temperature range. The thickening agent will typically be used in an amount of from about 0.1 to about 12% by weight, preferably from about 1 to about 8% by weight, and most preferably
20 from about 2 to about 4% by weight, based on the weight of the composition.

In some cases it is desirable to package the cleaning compositions, according to the invention, in cans, such as aerosol cans to facilitate application of the cleaning compositions in the field. Cans, and particularly

aerosol cans, are generally made from steel, so are susceptible to corrosion by products containing water. Products containing water, such as the composition according to the invention, require the addition of a corrosion inhibitor to prevent corrosion of the can and contamination of the formulation in the can. When the formulation according to the invention is in the form of a microemulsion, the microemulsion is susceptible to destabilization by the addition of ions to the formulation. It is therefore necessary to use a corrosion inhibitor that will not contribute to the destabilization of the microemulsion. Corrosion inhibitors that are compatible with the microemulsion composition according to the invention must be selected such that they do not contribute an amount of ions to the formulation that will destabilize the microemulsion. Preferably the inhibitor will be a molecule that has both an oil soluble portion and a water soluble portion. It has been found that an amphoteric surfactant containing an amine functionality in an amount of from about 0.05% to about 2% by weight, and preferably from about 0.25% to about 1.0%, acts as a corrosion inhibitor when combined with the microemulsion composition according to the invention, does not break the microemulsion and is effective in prevention of corrosion. Examples of suitable corrosion inhibitors include the DERIPHAT® amphoteric surfactants, particularly advantageous is DERIPHAT® 151-C, available from Henkel Corporation, Ambler PA. Other corrosion inhibitors that can be used with the composition according to the invention include, but are not limited to, amine soaps of fatty acids and fatty alkanolamides such as the C₈ to C₁₈ fatty alkanolamides, examples of which

include STANDAMID® alkanolamides, available from Henkel Corporation.

As set forth above, the precise amount of alkyl ester solvent in general, and methyl ester solvent, in particular, present in the composition depends on the type of cleaning to be performed. Hence, if a hard surface is to be completely stripped of any and all coatings thereon, the amount of methyl ester solvent present in the composition will range from about 50 to about 95% by weight, based on the weight of the composition. Similarly, if an undesirable substance, such as graffiti, is to be removed from a coated hard surface without damaging the underlying coating, the amount of methyl ester solvent present in the composition will range from about 15 to about 50% by weight, based on the weight of the composition.

However, another variable associated therewith is the dwell-time of the composition. Thus, if a hard surface is to be completely stripped of any coating substances, as is the case in paint stripping, the dwell-time of the composition on the hard surface will range from about 20 to about 45 minutes.

On the other hand, if an undesirable substance, such as graffiti, is to be removed from a coated hard surface without damaging the underlying coating, the dwell time of the composition on the hard surface will range from about 2 to about 20 minutes.

The present invention will be better understood by the examples which follow, all of which are intended for illustrative purposes only, and are not meant to unduly limit the scope of the invention in any way. Unless otherwise

indicated, percentages are on a weight-by-weight basis.

EXAMPLES

A terpene-free cleaning composition was prepared in accordance with
5 the present invention. Its formulation is found in Table 1, below.

Table 1

Component	%wt.
C8-C10 methyl ester	46.5
isopropylamine salt of LAS acid	7.1
propylene glycol n-butyl ether	9.0
C12-C14 sodium FAS (29%)	5.3
water	32.1

10

The physical characteristics of the above-disclosed composition are
found in Table 2, below.

15

Table 2

Characteristic	Value
pH (as is)	6.0-8.5
%solids (1 hour, vacuum oven)	8.3-9.8
Specific Gravity, 25°C	0.91-0.95
Cloud Point, lower	50°F max
Cloud Point, upper	160°F min
Appearance, 1 cm test tube	clear liquid

The formulation described in Table 1 was found to be effective in removing graffiti (acrylic spray paint) from a variety of non-porous substrates. A particular advantage of the formulation described in Table 1 is that it can be used to remove cured acrylic spray paint (graffiti) which has been applied over polyurethane paint, without damaging the underlying polyurethane paint. Most conventional graffiti removers will not only remove the undesired graffiti, but also remove or damage the desired underlying paint, resulting in the additional expense of repainting the substrate.

The formulation described in Table 1 also has the following advantages over conventional graffiti removers:

1. Low toxicity
2. Readily biodegradable

3. Primarily naturally derived
4. Low volatility

A second terpene-free cleaning composition was prepared in accordance with the present invention. Its formulation is found in Table 3, below.

Table 3

Component	% wt
C ₈₋₁₀ methyl ester	30.8
cyclohexanone	15.2
isopropylamine salt of LAS acid	8.4
propylene glycol n-butyl ether	9.3
sodium lauryl sulfate (29%)	4.0
sodium octyl sulfate (40%)	1.3
water	31.0

The physical characteristics of the above-disclosed composition are found in Table 4, below.

Table 4

Characteristic	Value
pH (as is)	6.3
%solids (1 hour, vacuum oven)	9.36
Specific Gravity, 25°C	0.942
Cloud point, lower	46°F max
Cloud point, upper	128°F min
Appearance, 1 cm test tube, 25°C	clear liquid

WHAT IS CLAIMED IS:

1. A terpene-free cleaning composition comprising:
 - (a) a C₁₋₄ alkyl ester of a C₆₋₂₂ saturated or unsaturated carboxylic acid;and
 - (b) a cyclic ketone, wherein (a) and (b) are employed at a ratio by weight of from about 10:1 to about 1:10.
2. The composition of claim 1 wherein the C₁₋₄ alkyl ester of a C₆₋₂₂ saturated or unsaturated carboxylic acid is a C₆₋₁₄ methyl ester.
3. The composition of claim 1 wherein the C₁₋₄ alkyl ester of a C₆₋₂₂ saturated or unsaturated carboxylic acid is a C₈₋₁₀ methyl ester.
4. The composition of claim 1 wherein the cyclic ketone is cyclohexanone.
5. The composition of claim 1 wherein (a) and (b) are employed at a ratio by weight of about 2:1.
6. A process for removing a coating from a substrate comprising contacting the coating with the composition of claim 1.
7. The process of claim 7 wherein the coating has a polymer matrix.
8. A terpene-free cleaning composition comprising:
 - (a) from about 2 to about 12% by weight of an oil-soluble anionic surfactant;
 - (b) from about 0.2 to about 6% by weight of a water-soluble anionic surfactant;
 - (c) from about 3 to about 96% by weight of a primary solvent consisting

of a C₁₋₄ alkyl ester of a C₆₋₂₂ saturated or unsaturated carboxylic acid;

(d) from about 2 to about 14% by weight of a short-chain cosurfactant;

and

(e) remainder, water, all weights being based on the total weight of the composition.

9. The composition of claim 8 wherein the oil-soluble anionic surfactant is selected from the group consisting of amine salts of dodecylbenzenesulfonic acid, calcium salts of dodecylbenzenesulfonic acid, phosphate esters and mixtures thereof.

10. The composition of claim 8 wherein the oil-soluble anionic surfactant is the isopropylamine salt of dodecylbenzenesulfonic acid.

11. The composition of claim 8 wherein the oil-soluble anionic surfactant is present in the composition in an amount of from about 6 to about 8% by weight, based on the weight of the composition.

12. The composition of claim 8 wherein the water-soluble anionic surfactant is selected from the group consisting of alkali metal salts of fatty acids, organic base salts of fatty acids, alkyl sulfates, alkyl ether sulfates, alkyl aromatic sulfonates, alkyl sulfonates, alpha olefin sulfonates, sulfosuccinates, and mixtures thereof.

13. The composition of claim 8 wherein the water-soluble anionic surfactant is C₈₋₁₄ fatty alcohol sulfate.

14. The composition of claim 8 wherein the water-soluble anionic surfactant is present in the composition in an amount of from about 1 to about

2% by weight, based on the weight of the composition.

15. The composition of claim 8 wherein the primary solvent is a C_8 - C_{10} methyl ester.

16. The composition of claim 8 wherein the primary solvent is present in the composition in an amount of from about 40 to about 50% by weight, based on the weight of the composition.

17. The composition of claim 8 wherein the short-chain cosurfactant is selected from the group consisting of C_3 - C_6 alcohols, glycols, glycol ethers, pyrrolidones, glycol ether esters, and mixtures thereof.

18. The composition of claim 8 wherein the short-chain cosurfactant is propylene glycol n-butyl ether.

19. The composition of claim 8 wherein the short-chain cosurfactant is present in the composition in an amount of from about 8 to about 10% by weight, based on the weight of the composition.

20. The composition of claim 8 wherein the composition has a pH value of less than about 9.

21. The composition of claim 8 wherein the composition has a thermal stability ranging from about 10 to about 70°C.

22. The composition of claim 8 wherein the primary solvent and water are present in the composition in a ratio by weight ranging from about 50:1 to about 1:4.

23. The composition of claim 8 wherein the primary solvent and water are present in the composition in a ratio by weight of about 1.5:1.

24. The composition of claim 8 further comprising a cyclic ketone.
25. The composition of claim 24 wherein the cyclic ketone is cyclohexanone.
26. The composition of claim 24 wherein the cyclic ketone is present in the composition in an amount of from about 1 to about 35% by weight, based on the weight of the composition.
27. The composition of claim 24 wherein the cyclic ketone is present in the composition in an amount of from about 10 to about 20% by weight, based on the weight of the composition.
28. The composition of claim 24 wherein the primary solvent and cyclic ketone are present in the composition in a ratio by weight of from about 10:1 to about 1:10.
29. The composition of claim 24 wherein the primary solvent and cyclic ketone are present in the composition in ratio by weight of about 2:1.
30. A terpene-free cleaning composition comprising:
- (a) from about 6 to about 8% by weight of an isopropylamine salt of dodecylbenzenesulfonic acid.
 - (b) from about 1 to about 2% by weight of a C₁₂₋₁₄ fatty alcohol sulfate;
 - (c) from about 40 to about 50% by weight of a primary solvent consisting of a C₈-C₁₀ methyl ester;
 - (d) from about 8 to about 10% by weight of a propylene glycol n-butyl ether and
 - (e) remainder, water, all weights being based on the total weight of the

composition, and wherein the primary solvent and water are present in the composition in a ratio by weight of about 1.5:1.

31. The composition of claim 30 further comprising from about 1 to about 35% by weight of a cyclic ketone.

32. The composition of claim 31 wherein the cyclic ketone is cyclohexanone.

33. A process for cleaning a hard surface comprising contacting the surface with a cleaning-effective amount of a terpene-free cleaning composition containing:

(a) from about 2 to about 12% by weight of an oil-soluble anionic surfactant;

(b) from about 0.2 to about 6% by weight of a water-soluble anionic surfactant;

(c) from about 3 to about 96% by weight of a primary solvent consisting of a C_{1-4} alkyl ester of a C_{6-22} saturated or unsaturated carboxylic acid;

(d) from about 2 to about 14% by weight of a short-chain cosurfactant; and

(e) remainder, water, all weights being based on the total weight of the composition.

34. The process of claim 33 wherein the oil-soluble anionic surfactant is selected from the group consisting of amine salts of dodecylbenzenesulfonic acid, calcium salts of dodecylbenzenesulfonic acid, phosphate esters, and mixtures thereof.

35. The process of claim 33 wherein the oil-soluble anionic surfactant is the isopropylamine salt of dodecylbenzenesulfonic acid.
36. The process of claim 33 wherein the oil-soluble anionic surfactant is present in the composition in an amount of from about 6 to about 8% by weight, based on the weight of the composition.
37. The process of claim 33 wherein the water-soluble anionic surfactant is selected from the group consisting of alkali metal salts of fatty acids, organic base salts of fatty acids, alkyl sulfates, alkyl ether sulfates, alkyl aromatic sulfonates, alkyl sulfonates, alpha olefin sulfonates, sulfosuccinates, and mixtures thereof.
38. The process of claim 33 wherein the water-soluble anionic surfactant is a C12-C14 fatty alcohol sulfate.
39. The process of claim 33 wherein the water-soluble anionic surfactant is present in the composition in an amount of from about 1 to about 2% by weight, based on the weight of the composition.
40. The process of claim 33 wherein the primary solvent is a C₈-C₁₀ methyl ester.
41. The process of claim 33 wherein the primary solvent is present in the composition in an amount of from about 40 to about 50% by weight, based on the weight of the composition.
42. The process of claim 33 wherein the short-chain cosurfactant is selected from the group consisting of C₃-C₆ alcohols, glycols, glycol ethers, pyrrolidones, glycol ether esters, and mixtures thereof.

43. The process of claim 33 wherein the short-chain cosurfactant is propylene glycol n-butyl ether.
44. The process of claim 33 wherein the short-chain cosurfactant is present in the composition in an amount of from about 8 to about 10% by weight, based on the weight of the composition.
45. The process of claim 33 wherein the composition has a pH value of less than about 9.
46. The process of claim 33 wherein the composition has a thermal stability ranging from about 10 to about 70°C.
47. The process of claim 33 wherein the primary solvent and water are present in the composition in a ratio by weight ranging from about 50:1 to about 1:4.
48. The process of claim 33 wherein the primary solvent and water are present in the composition in a ratio by weight of about 1.5:1.
49. The process of claim 33 wherein the terpene-free cleaning composition further comprises from about 1 to about 35% by weight of a cyclic ketone.
50. The process of claim 49 wherein the cyclic ketone is cyclohexanone.
51. The composition of claim 8 further comprising a thickening agent.
52. The composition of claim 51 wherein the thickening agent is tetraalkyl ammonium bentonite.
53. The process of claim 33 wherein the cleaning composition further contains a thickening agent.
54. The process of claim 53 wherein the thickening agent is tetraalkyl

ammonium bentonite.

ABSTRACT OF THE DISCLOSURE

A terpene-free cleaning composition containing: (a) an oil-soluble anionic surfactant; (b) a water-soluble anionic surfactant; (c) a primary solvent consisting of a C₁₋₄ alkyl ester; (d) a short-chain cosurfactant; and (e) water.

5

Cognis Corporation, Patent Dept.
2500 Renaissance Blvd., Suite 200
Gulph Mills, PA 19406

SJT/mc

Type a plus sign (+) inside this box → ☐

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

0010/PTO Rev. 6/95	U.S. Department of Commerce Patent and Trademark Office	Attorney Docket Number	M 6636 CC/CSAP
<h2 style="margin: 0;">DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION</h2>		First Named Inventor	Gross, Stephen F.
		COMPLETE IF KNOWN	
		Application Number	
		Filing Date	
		Group Art Unit	
		Examiner Name	

☒ Declaration Submitted with Initial Filing
 OR
 ☐ Declaration Submitted after Initial Filing

As a below named inventor, I hereby declare that
 My residence, post office address, and citizenship are as stated below next to my name
 I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below)
 of the subject matter which is claimed and for which a patent is sought on the invention entitled

GRAFFITI REMOVER, PAINT STRIPPER, DEGREASER

(Title of the Invention)

the specification of which

☒ is attached hereto

OR

☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International

Application Number and was amended on (MM/DD/YYYY) (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, § 1.56

I hereby claim foreign priority benefits under Title 35, United States Code §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT International application having a filing date before that of the application on which priority is claimed

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority sheet attached hereto

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below

Application Number(s)	Filing Date (MM/DD/YYYY)	Additional provisional application numbers are listed on a supplemental priority sheet attached hereto
60/155,330	09/22/1999	

Burden Hour Statement This form is estimated to take 4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Washington DC 20231.

Type a plus sign (+) inside this box → ☐

M 6636 CC/CSAP

DECLARATION**Page 2**

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365© of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code §112 1 acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application

U.S. Parent Application Number	PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority sheet attached hereto

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith

☐ Firm Name Customer Number or label
OR

☒ List Attorney(s) and/or agent(s) name and registration number below

Name	Registration Number	Name	Registration Number
John E. Drach	32,891	Steven J. Trzaska	36,296
Aaron E. Ettelman	42,516	Henry E. Millson, Jr.	18,980

☐ Additional attorney(s) and/or agent(s) named on a supplemental sheet attached hereto

Please direct all correspondence to: ☒ Customer Number or label **23657** OR ☐ Fill in correspondence address below

Name	Steven J. Trzaska		
Address			
Address			
City	State	Zip	
Country	Telephone	610-278-4929	Fax 610-278-6548

hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor							
Given Name	Stephen	Middle Initial	F.	Family Name	Gross	Suffix e.g. Jr.			
Inventor's Signature					Date				
Residence: City	Souderton	State	PA	Country	USA	Citizenship	USA		
Post Office Address	152 Chester Court								
Post Office Address									
City	Souderton	State	PA	Zip	18964	Country	USA	Applicant Authority	

☒ Additional inventors are being named on supplemental sheet(s) attached hereto

Type a plus sign (+) inside this box → ☐

M 6636 CC/CSAP

DECLARATION					ADDITIONAL INVENTOR(S) Supplemental Sheet				
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor				
Given Name	Martin	Middle Initial	J.	Family Name	Barabash	Suffix e.g. Jr.			
Inventor's Signature						Date			
Residence: City	Jamesburg	State	NJ	Country	USA	Citizenship	USA		
Post Office Address	One Sawgrass Court								
Post Office Address									
City	Jamesburg	State	NJ	Zip	08831	Country	USA	Applicant Authority	
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor				
Given Name	J. Frederick	Middle Initial		Family Name	Hessel	Suffix e.g. Jr.			
Inventor's Signature						Date			
Residence: City	Doylestown	State	PA	Country	USA	Citizenship	USA		
Post Office Address	2097 Country Club Drive								
Post Office Address									
City	Doylestown	State	PA	Zip	18901	Country	USA	Applicant Authority	
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor				
Given Name		Middle Initial		Family Name		Suffix e.g. Jr.			
Inventor's Signature						Date			
Residence: City		State		Country		Citizenship			
Post Office Address									
Post Office Address									
City		State		Zip		Country		Applicant Authority	
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor				
Given Name		Middle Initial		Family Name		Suffix e.g. Jr.			
Inventor's Signature						Date			
Residence: City		State		Country		Citizenship			
Post Office Address									
Post Office Address									
City		State		Zip		Country		Applicant Authority	
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor				
Given Name		Middle Initial		Family Name		Suffix e.g. Jr.			
Inventor's Signature						Date			
Residence: City		State		Country		Citizenship			
Post Office Address									
Post Office Address									
City		State		Zip		Country		Applicant Authority	
<input type="checkbox"/> Additional inventors are being named on supplemental sheet(s) attached hereto									